

Technical Data Sheet

NORC ENORM-C3 *db* **SAE 5W30 ACEA C3** **Fully Synthetic Engine Oil**

PRODUCT DESCRIPTION

NORC ENORM-C3 db SAE 5W-30 is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. NORC additive technology reduces carbon or sludge build up even under severe driving conditions.

NORC ENORM-C3 db SAE 5W-30 is manufactured using highest quality fully synthetic base stocks and state of the art additive technology. This ensures a finished product with unmatched performance level.

NORC ENORM-C3 db SAE 5W-30 is designed for an advanced passenger car and diesel engines, both turbocharged and non-turbocharged including engines with diesel particulate filters (ACEA C3).

BENEFITS

- Improve engine efficiency and longevity
- Excellent wear and high heat protection
- Excellent viscosity retention
- Excellent engine protection under harsh driving conditions
- Long drain interval
- Reduce carbon sludge build up
- Low oil & fuel consumption
- Improve engine efficiency and longevity
- Superior low friction characteristics

Technical Data Sheet

NORC ENORM-C3 *db* **SAE 5W30 ACEA C3** **Fully Synthetic Engine Oil**

SPECIFICATIONS

API SN/CF
ACEA A3 / B4 / C3
BMW LL-04
MB 229.51
GM DEXOS 2
VW 502.00 / 505.00 / 505.01

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	SAE 5W30
Density @ 15°C	Kg/L	ASTM D4052-09	0.8514
Kinematic Viscosity @ 40°C	Cst	ASTM D445-10	69.38
Kinematic Viscosity @ 100°C	Cst	ASTM D445-10	11.56
Viscosity Index		ASTM D2270-04	162
Flash Point, COC	°C	ASTM D92-05A (10)	> 220
Pour point	°C	ASTM D97-09	< -42

The above data is just an indication based on production, and does not considered to be actual specification.
"NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.