

Technical Data Sheet

NORC ENORM *db* **SAE 5W-50 API SN/CF** **Fully Synthetic Engine Oil**

PRODUCT DESCRIPTION

NORC ENORM *db* SAE 5W-50 is a fully synthetic based formulation that protects against friction, heat and corrosion, keeping engines healthy and efficient. NORC additive technology reduces carbon or sludge build up even under severe driving conditions, and optimally suited for high stress environments.

NORC ENORM *db* SAE 5W-50 is manufactured using highest quality fully synthetic base stocks and state of the art additive technology. The modern manufacturing process ensures a top quality finished product.

NORC ENORM *db* SAE 5W-50 is designed for an advanced passenger car and diesel engines, both turbocharged and non-turbocharged.

BENEFITS

- Excellent Wear & High Heat Protection
- Excellent Viscosity Retention
- Excellent Engine Protection Under Harsh Driving Conditions
- Long Drain Interval
- Reduce Carbon Sludge Build-up
- Low Oil & Fuel Consumptions
- Superior Low Friction Characteristics
- Improve engine efficiency and longevity

Technical Data Sheet

NORC ENORM *db* **SAE 5W-50 API SN/CF** **Fully Synthetic Engine Oil**

SPECIFICATIONS

API SN/CF
ACEA A3 / B3 / B4
MB 229.3
VW 502.00 / 505.00
PORSCHE A40
BMW LL-01

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	SAE 5W50
Density @ 15°C	Kg/L	ASTM D4052	0.854
Kinematic Viscosity @ 40°C	Cst	ASTM D445	156
Kinematic Viscosity @ 100°C	Cst	ASTM D445	25
Viscosity Index		ASTM D2270	194
Flash Point, COC	°C	ASTM D92-05A	> 235
Pour point	°C	ASTM D97	< -36

The above data is just an indication based on production, and does not considered to be actual specification.
"NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.