

Technical Data Sheet

NORC TAKT *db* **SAE 10W30 API SN/CF** **Semi Synthetic Engine Oil**

PRODUCT DESCRIPTION

NORC TAKT *db* SAE 10W30 is a high performance light-running semi synthetic lubricating engine oil designed for use in modern engines. It delivers excellent performance, protection and fuel economy properties.

NORC TAKT *db* SAE 10W30 is precisely developed and formulated with an advanced additive technology to ensure excellent engine cleanliness, viscosity retention and thermal stability under different driving conditions.

NORC TAKT *db* SAE 10W30 fulfills or exceeds the service a requirement of API SN/CF and it is an ideal choice for most benzin and diesel engines, including turbo-charged and non-turbocharged engines, and can be used year round in most climates.

BENEFITS

- Excellent wear and high heat protection
- Excellent Viscosity retention
- Excellent engine protection under different driving conditions
- Low oil & fuel consumptions
- Excellent Low friction characteristics
- Thermal Stability
- Enhanced anti-wear properties
- Improved engine cleanliness
- Improved engine efficiency and performance

Technical Data Sheet

NORC TAKT *db* **SAE 10W30 API SN/CF** **Semi Synthetic Engine Oil**

SPECIFICATIONS

API SN/CF
ACEA A3/B3/B4
MB 229.1
VW 501.01/505.00

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	SAE 10W30
Color		ASTM D1500	< 3.5
Density @ 15°C	Kg/L	ASTM D4052	0.863
Kinematic Viscosity @ 40°C	Cst	ASTM D445	67.5
Kinematic Viscosity @ 100°C	Cst	ASTM D445	14.5
Viscosity Index		ASTM D2270	144
Flash Point, COC	°C	ASTM D92-05A	> 210
Pour point	°C	ASTM D97	< -36

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.