

Technical Data Sheet

NORC TAKT *db* **SAE 5W40 API SN/CF** **Semi Synthetic Engine Oil**

PRODUCT DESCRIPTION

NORC TAKT *db* SAE 5W40 is high performance semi synthetic engine oil designed for use in modern engines giving improved quietness and fuel consumption. Its unique formulation provides excellent performance, protection, fuel economy properties, and sustain horsepower and torque throughout the life of your engine with regular use.

NORC TAKT *db* SAE 5W40 is premium synthetic blend multi-grade engine oil, precisely developed and formulated with advanced additive technology to ensure excellent viscosity retention and thermal stability under all driving conditions.

NORC TAKT *db* SAE 5W40 fulfills or exceeds the service requirements of API SN/CF and it is excellently suited for use in passenger cars and light trucks, equipped with benzin and diesel engines, both turbocharged and non-turbocharged.

BENEFITS

- Excellent for use in engines with tight tolerances
- Excellent viscosity retention
- Excellent engine protection under different driving conditions
- Long drain intervals
- Low fuel consumption
- Low oil consumption
- Excellent oxidation resistance

Technical Data Sheet

NORC TAKT *db* **SAE 5W40 API SN/CF** **Semi Synthetic Engine Oil**

SPECIFICATIONS

API SN/CF
ACEA A3/B4
MB 229.3
BMW LL-01
VW 502.00/505.00
PORSCHE A40
PSA B71 2296

TECHNICAL DATA SHEET

PROPERTY	UNIT	TEST METHOD	SAE 5W40
Density @ 15°C	Kg/L	ASTM D4052	0.856
Kinematic Viscosity @ 40°C	Cst	ASTM D445	89.7
Kinematic Viscosity @ 100°C	Cst	ASTM D445	14.1
Viscosity Index		ASTM D2270	162
Flash Point, COC	°C	ASTM D92-05A	> 200
Pour point	°C	ASTM D97	< -39

The above data is just an indication based on production, and does not considered to be actual specification. "NANO OIL REFINING COMPANY NORC GmbH" holds its right to make modifications.